



S U P P L E M E N T A L / B I D B U L L E T I N
No. 01, s. 2022

Name of Project : Smart Campus Development, Operationalization of Face to Face Classes and Upgrading/Procurement of Equipment (*ICT Equipment*)
Contract ID No. : 22PBGNMSC15.1 - G
PhilGEPS Reference No. : 9076354
Date of issuance : October 12, 2022

In accordance with Section 22.5.2 of IRR of R.A. No. 9184, this Bid Bulletin No. 01 – 2022 is hereby issued to clarify/amend the following:

Description	Clarification/Amendment
<u>Section VIII. Technical Specification</u>	
Network Switch (8 Ports)	PoE Interfaces: minimum of 4 port PoE/PoE+ Networking Interfaces: 10/100/1000 Mbps Ethernet RJ45 Ports Modes: Layer 2 PoE Gigabit Ethernet Switch
4U Data Cabinet	With PDU
Network Switch (24 Ports)	PoE switch with (16) GbE RJ45 ports, including (8) PoE+ ports, and (2) 1G SFP ports. Networking Interfaces: (16) 10/100/1000 RJ45 Ports (2) 1G SFP Ethernet Ports
Network Switch (16 Ports)	PoE switch with (16) GbE RJ45 ports, including (8) PoE+ ports, and (2) 1G SFP ports. Networking Interfaces: (16) 10/100/1000 RJ45 Ports (2) 1G SFP Ethernet Ports
UTP Cable (Cat 6)	1 box / 305M
Cable Duct (2x) (2m)	PVC SLOTTED CABLE DUCT AD-2.2L 2"x2"x2M
Cat 6 STP Cable	1 box - 305 meters
Access Point	Ceiling-mounted WiFi 6E access point designed to provide seamless, multi-band coverage within high-density client environments. Features: WiFi 6 support (2.4/5/6 GHz bands)

BIDS AND AWARDS COMMITTEE

Labuyo, Tangub City, Misamis Occidental, Philippines 7214
088-586-0170/09667707473 | www.nmsc.edu.ph | bacsecoffice@nmsc.edu.ph



<p>IP Phone</p>	<p>Powered with PoE+ 2 SIP accounts, 2 line keys, 3-way conferencing, 3 XML programmable context-sensitive soft keys HD audio on speakerphone and handset Dual-switched Gigabit ports, integrated PoE With speed dial keys Up to 1000 contacts, call history up to 200 records</p>
<p>RFID Reader Specification: Interface: USB</p>	<p>USB Plug and Play. 0-80mm Reading Distance. Frequency: 13.56MHz. Baud Rate: 9600. Reading time: <0.5s. Power Supply: +5V DC. Consume Current: 70mA.</p>
<p>QR Code Scanner Specification: Interface: USB</p>	<p>Point-and-shoot Scanning Simplicity--- With omni-directional scanning. Workers can scan qr codes across a wide range (0.5 in./1.23 cm to 14.5 in./36.8 cm). Interface: USB</p>
<p>CCTV Camera IP Specification: POE, 6MP, IP67</p>	<p>Specification: POE Water and dust resistant (IP67) MP resolution (3200 × 1520) Up to 40m IR Light Range</p>

Other specifications/requirements in the original Terms of Reference (TOR) and/or Manual Bidding Documents of the project are retained.

This clarification /addendum is hereby made as an integral part of the Terms of Reference (TOR)/Manual of Bidding Documents for the aforesaid project.

Please be guided accordingly.



[Signature]
JOEL R. DAGOT, Ed. D.
BAC Vice - Chairperson

BIDS AND AWARDS COMMITTEE